



# HANDLING & STORAGE EQUIPMENT

## PLATE HEATER, SELF-LEVELING HEATED DISPENSER

PROJECT NAME:

LOCATION:

ITEM NO:

QTY:

MODEL NO:

AIA NO:

SIS NO:

CSI SECTION:

### AVAILABLE MODELS:

- ALC PLH2
- ALC PLH3

### STANDARD FEATURES:

- Stainless steel is nickel-bearing, 200 series minimum, NSF recognized for corrosion resistance
- Plate Sizes: Accommodates dishes ranging from 7" to 10-1/4"
- 208/220 VAC, 60 Hz, single phase, six foot grounded 20 amp power cord supplied
- (4) 5" non-marking poly swivel casters - 2 with brake
- NEMA 6-20P plug

**CONSTRUCTION:** Stainless steel is nickel-bearing, 200 series minimum. This material is NSF recognized for corrosion resistance. The outer unit is constructed of 18 gauge stainless steel. Inner walls are constructed of .063 high strength aluminum. All sides and lids of unit are insulated with fiberglass insulation.

**LIDS:** Unique hat channel design requires no gaskets.

**HEATING SYSTEM:** Thermostatically controlled, forced air heating system with 3200 watt element.

**SELF-LEVELING DISPENSER:** Individual, removable, self-adjusting and all stainless steel construction. Self-lubricating bearings ride over vertical guide rods. Available stacking height is 27-1/4".

**ORIGIN OF MANUFACTURE:** Designed and manufactured in the United States.

ALC PLH2 Model shown.








### OPTIONS/ACCESSORIES:

- 240VAC



Top Views



<b>Model No.</b>	ALC PLH2	ALC PLH3
<b>Width</b>	33-3/8"	43-7/16"
<b>Depth</b>	23-3/4"	23-3/4"
<b>Height</b>	42-3/4"	42-3/4"
<b>Caster Type</b>	4 Swivel, 2 w/Brake	4 Swivel, 2 w/Brake
<b>Caster Diameter</b>	5"	5"
<b>Watt</b>	3200	3200
<b>Amp</b>	16.3 & 15	16.3 & 15
<b>Volt</b>	208/220, 60Hz & 240	208/220, 60Hz & 240
<b>Thermostat Range</b>	135 - 175°F	135 - 175°F
<b>Case Cu. Ft.</b>	24	31.1
<b>Ship Wt. (lbs)</b>	270	335