



# CUSTOM

## OPEN BASE ELECTRIC HOT FOOD TABLE MODEL 33000

Open shelving base hot food table with 16 gauge stainless top, and integral backsplash with 45° return. Individual die-stamped 12 x 20 top openings, common water bath tank with thermostatically controlled external heating elements, and 8" deep plate shelf. Drain, gate valve, and fill faucet provided. 6" high adjustable and movable legs.

PROJECT NAME:

LOCATION:

ITEM NO:

QTY:

MODEL NO:

AIA NO:

SIS NO:

CSI SECTION: 11400

### AVAILABLE MODELS:

- 33330
- 33348
- 33360
- 33372
- 33386

### STANDARD FEATURES:

- Available under one piece top with other modular equipment up to 16' in length
- 6" high legs—adjustable and movable
- Thermostatic control for precise food temperatures
- Available for 208 or 240 volt operation only
- Heating elements mounted beneath tank to avoid troublesome cut outs in tank body.
- Individual die-stamped 12 x 20 openings hold pans above common bath tank
- Drain, gate valve and swivel fill faucet provided
- 45° integral stainless backsplash providing access to electrical chase is standard. 90° stainless backsplash is optional.

**UNIT TOP:** Top to be one piece of die formed 16 gauge stainless steel with 2 5/8" nosing. Backsplash to be coved cornered, with 45° return at top and overall height of 6 3/4". Ends at top fitted with recessed heavy duty steel bars for field bolting units together, producing a hairline seam. Top stamped with individual 12 x 20 die formed raised perimeter openings. Swivel fill faucet provided. Unit with 8" deep, removable 18 gauge stainless steel plate shelf, and 8" wide x 1/2" thick, full length NSF composition workboard.

**FOOD WELLS:** 12" x 20" die formed raised perimeter openings in stainless steel top. Individual, thermostatically controlled, 3000 watt element(s), as required, mounted below one piece 18 gauge, 7" deep stainless steel water bath tank to heat food wells. 1" stainless steel drain nipple and gate valve provided.


**CONTROLS:** Unit comes standard with thermostatic control(s). Each control(s) has a lighted on/off switch that allows turning off of control(s) without moving temperature setting. Control(s) and elements mounted on front of 8" deep removable stainless steel plate shelf designed to allow easy access to elements, control(s) and elements pans. Connections to heating elements are located outside of heated zone to avoid wiring deterioration. Individual food wells wired to common junction box(es). Power cord is supplied.

**UNIT BASE:** Body ends to be die-formed stainless steel, finished and polished on the inside with corrosion resistant exterior. Insulated nosing and insulated back wall provided. Bottom shelf to be 22 gauge stainless steel with marine edge with integrally welded channel bracing, and 8" coved cornered turn up at rear. Legs to be 6" high stainless steel with adjustable bullet foot. Legs mounted to full length channel frame assembly which is integrally welded to bottom of body assembly. Legs can be moved left to right to avoid floor obstacles during installation.

**ORIGIN OF MANUFACTURE:** Designed and manufactured in the United States.

Open Base Electric Hot Food Table. Model shown with optional finished end.





**LEGEND FOR MODEL # 33000**  
 AFF=ABOVE FINISHED FLOOR  
 WL  
 FILL FAUCET WATER CONNECTION STUB FROM REAR OF UNIT  
 1/2" COPPER @ 24" AFF  
 DL  
 DRAIN LINE CONNECTION STUB FROM REAR OF UNIT TO 1/2" SWEAT FIT COPPER 19" AFF.

J-BOX 22" AFF  
 CHECK ONE:  
 208/60/1Ph  
 14.4Amps 3.0Kw  
 240/60/1Ph  
 12.5Amps 3.0Kw  
 HARDWARE CONNECTION

NOTE: ALL MECHANICALS ARE SHOWN IN APPROXIMATION LOCATION

29" Deep					
<b>Length</b>	30"	48"	60"	72"	86"
<b>Height*</b>	36"	36"	36"	36"	36"
<b>Wells</b>	2	3	4	5	6
<b>Elements</b>	1	1	2	2	2
<b>Ship Wt. (lbs)</b>	213	294	365	421	477
<b>208 Volt Models</b>					
<b>K.W.</b>	3	3	6	6	6
<b>Amps</b>	14.4	14.4	28.8	28.8	28.8
<b>240 Volt Models</b>					
<b>K.W.</b>	3	3	6	6	6
<b>Amps</b>	12.5	12.5	25	25	25

33" Deep					
<b>Length</b>	30"	48"	60"	72"	86"
<b>Model No.</b>	33330	33348	33360	33372	33386
<b>Height*</b>	36"	36"	36"	36"	36"
<b>Wells</b>	2	3	4	5	6
<b>Elements</b>	2	3	4	5	6
<b>Ship Wt. (lbs)</b>	213	294	365	421	477
<b>208 Volt Models</b>					
<b>K.W.</b>	3	3	6	6	6
<b>Amps</b>	14.4	14.4	28.8	28.8	28.8
<b>240 Volt Models</b>					
<b>K.W.</b>	3	3	6	6	6
<b>Amps</b>	12.5	12.5	25	25	25

\* All models with adjustable and movable legs for 35 1/2" to 36 3/4" work height.