



# PREP STATIONS

## SPECIALTY CUSTOM REMOTE WORKTOP FREEZER MODELS 64000

Remote freezer base with 16 gauge reinforced stainless steel top, and integral backsplash with 45° return. Stainless steel doors on concealed hinges. Condensing unit not provided. Evaporator blower coil with expansion valve supplied and installed. Unit with automatic defrost system and heated door frames. 6" high adjustable and movable legs.

**SHORT FORM SPEC:** Randell 64000 series model worktop freezer base with remote refrigeration system. Top to be 1 piece die formed stainless steel with corrosion resistant exterior body. Includes Randell evaporator blower coil fitted to base, complete with automatic defrost system, digital control, expansion valve and refrigeration lines installed for connection at rear of unit. Base interior ends and door openings shall be high impact ABS plastic with coved corner stainless steel interior to form bottom, back and top of cabinet. Base cabinet door to have ABS liner and include press-fit magnetic gaskets for positive sealing to ABS formed door opening frame complete with heater elements to prevent freezing. Unit to be shipped on standard 6" adjustable legs mounted to full length channel frame assembly allowing movement of legs to avoid floor obstacles.

### AVAILABLE MODELS:

- 64335
- 64338
- 64341
- 64352
- 64358
- 64364
- 64382

### STANDARD FEATURES:

- Available under one piece top with other modular equipment up to 16' in length
- 6" high legs—adjustable and movable
- Foamed in place "CFC free" urethane insulation
- Refrigeration system utilizes expansion valve and digital control for field adjustability
- Automatic coil defrost system
- 45° integral stainless backsplash is standard, 90° stainless backsplash is optional
- Precise temperature settings, LED temperature readout
- Filter dryer installed on liquid line
- Interior lighting inside the base cabinet

**CABINET EXTERIOR:** Top to be one piece of die formed 16 gauge stainless steel with 2 1/2" nosing. Backsplash to be coved cornered, with 45° return at top and overall height of 6 3/4". Ends at top fitted with recessed heavy duty steel bars for field bolting units together, producing a hairline seam. Exterior body to be corrosion resistant steel. Door opening frame to be ABS and contain magnetic strip for positive sealing of gaskets and heater elements to prevent gasket freezing. Back-up element installed. Work surface to be at 36" work height. Legs to be 6" high stainless steel with adjustable bullet foot. Legs mounted to full length channel frame assembly which is integrally welded to bottom of body assembly. Legs can be moved left to right to avoid floor obstacles during installation.

**CABINET INTERIOR:** Base interior to be ABS thermoplastic at ends only. Stainless steel interior liner to be coved cornered to form bottom, back and top. One baked enamel finished shelf provided behind each door. Unit insulation to be CFC free foamed in place urethane.

**DOORS:** Door fronts to be 22 gauge stainless steel with 16 gauge stainless steel handles, magnetic gaskets, ABS door liner and foamed in place insulation. Hinges are concealed, all stainless steel with bronze pivot pin in nylon bushing.

**REFRIGERATION:** Refrigerant to be specified by customer (Specification based on R-448a refrigerant). Interior fitted with Randell evaporator blower coil for cooling base. Expansion valve and refrigeration lines provided and installed for connection at unit rear. Blower coil fitted with expansion valve for fast recovery and automatic defrost heater system with digital control and safety switches. Condensing unit not provided. Unit totally prewired to junction box for 115V operation.



PROJECT NAME:	
LOCATION:	
ITEM NO:	
QTY:	
MODEL NO:	
AIA NO:	
SIS NO:	
CSI SECTION:	11400




### OPTIONS/ACCESSORIES:

- Stainless Steel Ends
- Stainless Steel Back
- Flat Top with No Backsplash
- Double Tier Drawers
- Tray Rack
- Intermediate Shelves
- Adjustable Shelves
- Laminate Fronts, Ends and Back
- Door/Drawer Locks
- White Poly Cutting Board, 1/2" or 3/4"
- Riclite Cutting Board, 1/2" or 3/4"


### ADDITIONAL RESOURCES:

- [Request A Quote](#)
- [Sales Tools](#)
- [Find A Rep](#)
- [KCL AutoCAD/Revit](#)





64335



64338




64341




MODEL	BASE SECTION(S)	L	D	H	STANDARD REF. BASE CONFIGURATION	BASE STORAGE CUBIC FT CAPACITY	VOLT/CYCLE/PHASE	AMPS	BTU LOAD	BUT EVAP.	SHIP WT.
<b>1 SECTION BASE STORAGE</b>											
<b>64335</b>	1	35	33	42.75	(1) 21" DOOR, 8" COIL	5.05	115/60/1	6	956	160	355
<b>64338</b>	1	38	33	42.75	(1) 24" DOOR, 8" COIL	5.98	115/60/1	6	1015	160	370
<b>64341</b>	1	41	33	42.75	(1) 27" DOOR, 8" COIL	6.91	115/60/1	6	1064	160	385


64352



64358





64364



MODEL	BASE SECTION(S)	L	D	H	STANDARD REF. BASE CONFIGURATION	BASE STORAGE CUBIC FT CAPACITY	VOLT/ CYCLE/ PHASE	AMPS	BTU LOAD	BUT EVAP.	SHIP WT.
<b>2 SECTION BASE STORAGE</b>											
<b>64352</b>	2	52	33	42.75	(2)21" DOORS	10.09	115/60/1	6	1536	160	445
<b>64358</b>	2	58	33	42.75	(2)24" DOORS	11.96	115/60/1	6	1635	160	475
<b>64364</b>	2	64	33	42.75	(2)27" DOORS	13.82	115/60/1	6	1734	160	505

64382



MODEL	BASE SECTION(S)	L	D	H	STANDARD REF. BASE CONFIGURATION	BASE STORAGE CUBIC FT CAPACITY	VOLT/ CYCLE/ PHASE	AMPS	BTU LOAD	BUT EVAP.	SHIP WT.
<b>3 SECTION BASE STORAGE</b>											
<b>64382</b>	3	82	33	42.75	(3)24" DOORS	17.93	115/60/1	6	2321	160	700


**DOORS:**

DOOR OPENING SIZES	CLEARANCES THROUGH DOOR		INTERIOR DEPTH BEHIND DOOR	ACCEPTS SHEET PAN SLIDES	OPTIONAL DRAWER PAN CAPACITY (PER DRAWER)
	DOOR WIDTH	LT. TO RT.	TOP TO BOTTOM		
21"	16 1/4"	20 1/4"	26.5"	No	(1) 12"x20"x6"
24"	19 1/4"	20 1/4"	26.5"	Yes	(1) 12"x20"x6" + (3) 1/9"
27"	22 1/4"	20 1/4"	26.5"	Yes	(2) 12"x20"x6"


\*Shelf depth is 25-1/4" on 33" deep equipment.

**OPTIONAL DRAWERS:**


21" Drawer:




24" Drawer:




27" Drawer:



32" Drawer:




**DIMENSIONAL DETAIL:**



LEGS ADJUSTABLE FROM: 6" - 7.125" SHOWN @ 6.75"

Stainless Steel Finished End:



Unfinished End:

