

SERVING STATIONS

SERVING LINE BREATH GUARD BENT MODELS RSB-DTSSFF

Designer series bent-corner breath guard: Double-tier, Single-sided, Non-adjustable front. Designed for full-service applications (bottom tier), self-service (top tier)

SHORT FORM SPEC: Randell designer series breath guard with bent corners. Double-tier, single sided, non-adjustable design for full service. Framework is constructed of 1" diameter stainless steel tubing with #4 "satin" finish. All glass panels shall be tempered with 1" radius corners and polished edges. Front and top panels utilize 3/8" thickness, end panels utilize 1/4" thickness. Provided with 3" x 1.25" surface mount flanges.

AVAILABLE MODELS:

RSB-DTSSFF-24 RSB-DTSSFF-30 RSB-DTSSFF-36 RSB-DTSSFF-48 RSB-DTSSFF-60 RSB-DTSSFF-72

NSF LISTED FINISH:

Stainless steel #4 finish

RSB-DTSSFF-86

Other finishes available (contact factory)

GLASS:

- Standard side glass is 1/4" tempered
- Standard top and front glass is 3/8" tempered (additional leg set required after reaching 66" maximum top glass length)

BREATH GUARD LENGTH GUIDE:

Unit Length	Center Line Length	Overall Length
24"	21.25"	23.75"
30"	27.25"	29.75"
36"	33.25"	35.75"
48"	45.25"	47.75"
60"	57.25"	59.75"
72"	69.25"	71.75"
86"	83.25"	85.75"
72"	69.25"	71.75"



PROJECT NAME:	
LOCATION:	
ITEM NO:	
QTY:	
MODEL NO:	
AIA NO:	
SIS NO:	
CSI SECTION:	11400



OPTIONS/ACCESSORIES:

LED lighting

Heatlamp

Combination: LED lighting and heatlamp

Dimension modification (Consult factory)

Alternative tubing finish (Consult factory)

ADDITIONAL RESOURCES:

Request A Quote
Sales Tools
Find A Rep











